

Panasonic uses an internationally recognized, independent research, engineering and evaluation laboratory who by contractual agreement with their clients does not allow the use of their name or logo because doing so may imply an endorsement of products or services. For this reason Panasonic has removed all references to said independent third party lab. Should you require the full unedited version, please contact your Panasonic representative.

Mechanical and Materials Engineering Division
July 31, 2009

SUMMARY OF TESTS PERFORMED

Project Number: 18.04481.16.101

Company: Panasonic Computer Solutions Company
Three Panasonic Way, 2F-12
Secaucus, NJ 07094
Attn: Angela MacNeill

Equipment Tested: Panasonic CF-30

Test Dates: May 2009 – July 2009

Notes: *The test item was evaluated for ability to boot into the Microsoft Windows® XP operating system following each of the tests described within this summary report. A listing of summarized tests and results appear in the accompanying table.*

Report Written By:



Eric Domes
Principal Engineer
Structural Dynamics and Product Assurance Section

Reviewed By:



Jenny Ferren
Manager
Structural Dynamics and Product Assurance Section



Summary of Tests Performed on the Panasonic CF-30

Test Description	Test Parameters	Test Results*
Altitude: Storage/Air Transport	MIL-STD-810G, Method 500.5, Procedure I <ul style="list-style-type: none"> 15,000ft Non-Operating 	Pass [†]
Altitude: Operation/Air Carriage	MIL-STD-810G, Method 500.5, Procedure II <ul style="list-style-type: none"> 15,000ft Operating 	Pass [†]
High Temperature: Storage	MIL-STD-810G, Method 501.5, Procedure I <ul style="list-style-type: none"> 160°F Non-Operating 	Pass [†]
High Temperature: Operation	MIL-STD-810G, Method 501.5, Procedure II <ul style="list-style-type: none"> 140°F Operating 	Pass [†]
High Temperature: Tactical—Standby to Operational	MIL-STD-810G, Method 501.5, Procedure III <ul style="list-style-type: none"> High storage (non-operating) to high operating (test for operation) Test results are for battery operation 	Pass
Low Temperature: Storage	MIL-STD-810G, Method 502.5, Procedure I <ul style="list-style-type: none"> -60°F Non-Operating 	Pass [†]
Low Temperature: Operation	MIL-STD-810G, Method 502.5, Procedure II <ul style="list-style-type: none"> -20°F Operating 	Pass [†]
Temperature Shock	MIL-STD-810G, Method 503.5, Procedure I <ul style="list-style-type: none"> From 200°F to -60°F, three cycles 	Pass [†]
Rain: Blowing	MIL-STD-810G, Method 506.5, Procedure I <ul style="list-style-type: none"> 5.8in/hr rain, 70mph wind, 30 minutes per surface Unit operating 	Pass
Rain: Drip	MIL-STD-810G, Method 506.5, Procedure III <ul style="list-style-type: none"> 15 minute exposure, drip test 	Pass [†]
Humidity	MIL-STD-810G, Method 507.5, Procedure II (Aggravated) <ul style="list-style-type: none"> Temp. cycles 86°F to 140°F; 95%RH 	Pass [†]
Sand and Dust: Dust	MIL-STD-810G, Method 510.5, Procedure I <ul style="list-style-type: none"> Blowing Dust (operating) Operating temperature of 140°F 	Pass [†]
Sand and Dust: Sand	MIL-STD-810G, Method 510.5, Procedure II <ul style="list-style-type: none"> Blowing Sand (operating) Operating temperature of 140°F 	Pass [†]
Explosive Atmosphere	MIL-STD-810G, Method 511.5, Procedure I	Pass [†]
Vibration: General Vibration - operating	MIL-STD-810G, Method 514.6, Procedure I (Transportation) <ul style="list-style-type: none"> Panasonic provided conditions (operating) 	Pass [†]
Vibration: General Vibration – non-operating	MIL-STD-810G, Method 514.6, Procedure I (Transportation) <ul style="list-style-type: none"> Category 24, general minimal integrity (non-operating) 	Pass [†]
Vibration: Loose Cargo Transportation	MIL-STD-810G, Method 514.6, Procedure II	Pass
Shock: Functional	MIL-STD-810G, Method 516.6, Procedure I <ul style="list-style-type: none"> 40g, 11ms Operating 	Pass [†]

* Full details will be provided in [REDACTED] Report Number 18.04481.16.100.FR2

[†] Test previously performed using comparable MIL-STD-810F procedure. See [REDACTED] Report 18.04481.09.FR3

[^] Test previously performed using comparable MIL-STD-810F procedure. See [REDACTED] Report 18.04481.09.201b

Test Description	Test Parameters	Test Results*
Shock: Transit-Drop 48-inch	MIL-STD-810G, Method 516.6, Procedure IV <ul style="list-style-type: none"> • 26 drops – 48in height on to 2in plywood – non operating • All drops performed on the same unit 	Pass
Shock: Transit-Drop 60-inch	MIL-STD-810G, Method 516.6, Procedure IV <ul style="list-style-type: none"> • 26 drops – 60in height on to 2in plywood – non operating • All drops performed on the same unit that was also subjected to all 48in drops 	Pass
Shock: Transit-Drop 72-inch	MIL-STD-810G, Method 516.6, Procedure IV <ul style="list-style-type: none"> • 26 drops – 72in height on to 2in plywood – non operating • All drops performed on the same unit that was also subjected to all 48in and all 60in drops 	Pass
Freeze / Thaw	MIL-STD-810G, Method 524, Procedure III (Rapid Temperature Change) <ul style="list-style-type: none"> • Test effects include condensation 	Pass
Vehicle Vibration	ASTM D4169-04 (99) Schedule E, Truck Assurance Level II, Operating	Pass

* Full details will be provided in XXXXXXXXXX Report Number 18.04481.16.100.FR2